



SURVIEW 4000




Semiconductor

Stud Bump	지름, 높이, 부피, 거칠기, 각도
CMP	Warpage, 거칠기
CVD	거칠기
Wafer	Warpage, 스크래치, 거칠기




PCB

Substrate (Pad, Trace, Space, Anchor, Land, Ball Pad, Via Hole, Dimple, SR)	높이, 폭, 깊이, 지름, 두께, 부피, 거칠기, Roundness
BGA	Ball 높이, 지름, Coplanarity



Display

Photo Space	지름, 높이, 폭, 부피
RGB	두께, 거칠기, BM 두께
TFT Pattern	높이, 폭, 거칠기
BLU	각도, 폭, 높이, 거칠기
Metal Jet	폭, 높이, 각도, 거칠기
Glass	Defect 형태, 폭, 높이,
OLED	증착 높이, 각도, 부피



기타

MEMS	높이, 폭
Precision machine part	거칠기, 높이, 폭
Laser Marking	깊이, 부피
Inkjet	부피, 높이, 면적
Micro Lens	곡률, 높이
RFID	높이, 폭, 거칠기

Specification

SURFIEW 4000

Vertical Resolution	VSI,VEI < 0.5nm, VPI < 0.1nm
Lateral Resolution	0.05~7.2um(Depends on magnification)
Height Repeatability	≤0.1% @ 1σ
Objective Lens	5 Selectable(Automatic)
Zoom Lens	3 Selectable(0.55x/0.75x/1.0x @ Automatic)
Camera Format	1/2" Mono Camera
Scan Method	Piezo Actuator@Capacity Closed loop
PZT Scan Range	≤150um
Scan Speed	7.5um/sec(1x) / 22.5um/sec(3x)
Illumination	White LED
Filter	Visible/Bandpass/Green Filter(Auto)
Auto Focus	Yes
X/Y Axis Stroke	300mm(X) x 300mm(Y)
Z Aixe Stroke	100mm
Tilt Aixe Stroke	± 6°
Work Table Size	350mm X 350mm
Max Workpiece Load	≤ 10kg
Layout Size	1780mm(W) x 960mm(D) x 1500mm(H)
Software	Surface View/Surface MAP@ Window10 (64bit)
Stitching	Yes
Vibration Isolation Platform	Passive Type(Vertical Resonance: 1.5Hz)
Input Power	2φ,110V/220V(± 10%), 50/60Hz

Option

Interference Lens	2.5x, 5.0x, 10x, 20x, 50x, 100x
Objective Lens	2.5x, 5.0x, 10x, 20x, 50x, 100x
Zoom Lens	0.55x, 0.75x, 1.0x, 1.5x, 2.0x
PZT Scan Range	≤300um
Motor Scan	≤10mm@Linear Scale
Laser Auto Focus	Option
Camera Format	2/3" or 1" Mono Camera
Work Table	Vacuum Table, Rotation Table



주식회사 지엘테크

대전광역시 대덕구 문평서로 18번길 77, 2동 3호(문평동)

T 042-934-2772 F 042-934-2773 E sales@gltech.kr www.gltech.kr